

# Dual Collar Gauge Carrier



## Description

The SST single Collar Gauge Carrier with bypass is designed to carry a single SST Sapphire Pz or single SST Quartz Qz gauge and allows the TEC to be connected to other carriers downhole as per well construction parameters. The gauge is attached directly to a gauge port with a high pressure metal to metal seal in our facility and is fully tested and qualified prior to sending to the field location. This carrier can be supplied in either 4130 or 13Cr versions and standard or premium connections. The Single Collar Gauge Carrier offers a lower cost system compared to the integral carrier system and is suitable for environments where long term pressure integrity is essential.

## Features

- Pressure and tensile integrity exceeds completion tubing performance
- Can be configured to monitor tubing or annulus pressure with either gauge at time of manufacture
- Metal to metal seal with gauge fully tested and qualified prior to delivery
- Available in a wide range of materials to be fully compatible with the completion design

## Applications

- Corrosive or HP permanent monitoring
- Reservoir optimization and characterization
- ESP (Electric Submersible Pump) monitoring and optimization
- Large bore drill stem testing
- HP fracturing operations monitoring

## Operating Specification

PRESSURE RATING	Exceeds customer specified tubing rating
MAKE UP LENGTH	60 in.
GAUGE TYPE	SST Sapphire Pz or SST Quartz Gauge
MATERIAL	4130-HRC22 or 13Cr – HRC22 as standard, Optional per customer requirement
END CONNECTION	API – EUE or VAM Top standard, other end connections per customer requirement

